

Horizons® 3G Point-Of-Use



HB 215i-SIP

Features

- Sleek design with electronic interface
- Elevated dispensing height and larger dispensing area
- Fold down drip tray for large containers
- Hot & cold temperature indicator
- Safety lock function for hot & cold water
- Fast flow electronic dispensing
- Accu-Temp - Serves water at the proper temperature every time
- Stay-Cool - Keeps the residual water in the cold waterway chilled and ready to serve
- SIP enhanced sanitization sanitizes cold reservoir, waterways and spout
- i-Boil - Increases the hot water temperature to just under boiling - perfect for coffee, teas, noodles, etc.
- Electronic shutoff and startup for extra energy savings during off hours
- 3 gallon reservoir
- Room for filters or RO inside
- Available in black or white
- UL certified



Models

H&C: HB 215i-SIP, HW 215i-SIP

Horizons® 3G

Power

Voltage (V)	115, 220, 100
Frequency (Hz)	50/60
Power Consumption	4.89A / 554W / 115V
Cold Power Consumption	1.44A / 118W / 115V
Hot Power Consumption	3.87A / 449W / 115V
ES (KWH/24hrs)	0.81
% lower than ES Standard	33%

Hot Water System

Avg. Hot Water Temp at nozzle @ 75°F ambient(Before/After On)	177.73°F / 188.17°F
Hot water ARI Rating	40 6oz > 165°F +/- 10%
Hot Thermostat / Heat Limiter	203°F +/-5.5°F
Hot Thermostat / Thermister Cycle	172° - 190°F
i-Boil Set Point	192°F
Avg. Temp of i-Boil at nozzle @ 75°F ambient (After On)	TBD
Hot Water Flow Rate	1.35 oz/sec
Hot Water Flow Rate (oz per sec)w/Accu-Temp delay	1.22 oz/sec
Hot Tank Size (L)	2L
Heat Band Wattage	450W

Cold Water System

Avg. Cold Water Temp at nozzle @ 75°F ambient(Before/After ON)	41.37°F / 41.57°F
Cold Water ARI Rating	29 5oz < 50°F +/-10%
Cold Thermostat Set Point	45°F +3°/-8°F
Cold Water Flow Rate	1.35 oz/sec
Cold Water Flow Rate (oz per sec)w/ Accu-Temp delay	1.22 oz/sec
Cold Tank Size / Usable Volume / Below Baffle Cold Water (Gal)	2.8 / 2.25 / 0.58 G

Weights and Measurements

Net Weight (Lbs)	54.67
Gross Weight (Lbs)	58.86
Cooler Dimensions / Boxed Dimensions WxDxH (inch)	12.5x15.3x44.6 / 13.2x16.2x45.7
Container Load (20')	186
Container Load (40')	383
Container Load (40' HC)	383
Container Load (45' HC)	432
Certifications	UL