

Stainless Steel Point-Of-Use



RS 115

RS 215

Features

- 430 grade stainless steel cabinet that is at home in today's kitchens
- Special smudge resistant finish
- Same reliable internal components as our Reflections® family
- High quality 1.2 Amp compressor chills water fast
- Energy Star rated 2.0L hot tank
- Removable, two-piece dishwasher safe drip tray
- Industry standard Tomlinson faucets
- 304 Stainless Steel reservoir
- Dual mechanical float for reliability
- UL listed

Models

H&C: RS215

C&C: RS115



Stainless Steel

Power

| | |
|--------------------------|---------------------|
| Voltage (V) | 115, 220, 100 |
| Frequency (Hz) | 50/60 |
| Power Consumption | 4.89A / 554W / 115V |
| Cold Power Consumption | 1.44A / 118W / 115V |
| Hot Power Consumption | 3.87A / 449W / 115V |
| ES (KWH/24hrs) | 1.14 |
| % lower than ES Standard | 5.0% |

Hot Water System

| | |
|---|------------------------------|
| Avg. Hot Water Temp at nozzle @ 75°F ambient(Before/After On) | 166.57°F / 191.43°F |
| Hot water ARI Rating | 45 6oz > 165°F +/- 10% |
| Hot Thermostat / Heat Limiter | 203°F +/-5.5°F |
| Hot Thermostat / Thermister Cycle | 167°F +/-11°F / 187°F +/-4°F |
| i-Boil Set Point | N/A |
| Avg. Temp of i-Boil at nozzle @ 75°F ambient (After On) | N/A |
| Hot Water Flow Rate | 0.96 oz/sec |
| Hot Water Flow Rate (oz per sec)w/Accu-Temp delay | N/A |
| Hot Tank Size (L) | 2.0L |
| Heat Band Wattage | 450W |

Cold Water System

| | |
|---|----------------------|
| Avg. Cold Water Temp at nozzle @ 75°F ambient(Before/After ON) | 45.87°F / 42.2°F |
| Cold Water ARI Rating | 27 5oz < 50°F +/-10% |
| Cold Thermostat Set Point | 45°F +3°/-8°F |
| Cold Water Flow Rate | 1.4 oz/sec |
| Cold Water Flow Rate (oz per sec)w/ Accu-Temp delay | N/A |
| Cold Tank Size / Usable Volume / Below Baffle Cold Water (Gal.) | 1 / 0.55 / 0.4 G |

Weights and Measurements

| | |
|---|-----------------------------|
| Net Weight (H&C / C&C Lbs.) | 29.0 / 27.0 |
| Gross Weight (H&C / C&C Lbs.) | 31.0 / 29.0 |
| Cooler Dimensions / Boxed Dimensions WxDxH (inch) | 13x13.1x38 / 13.2x13.3x38.6 |
| Container Load (20') | 238 |
| Container Load (40') | 490 |
| Container Load (40' HC) | 490 |
| Container Load (45' HC) | 546 |
| Certifications | UL |